

EDR1 Model Number Builder

Encrypted Video/Audio Diversity Receiver

Frequency Band

U1 = UHF Band	340.0-399.9 MHz
L1 = Lower L-Band	1435-1535 MHz
L2 = Upper L-Band	1700-1850 MHz
S1 = S-Band	2200-2399 MHz
S2 = ISM S-Band	2400-2499 MHz
S3 = Full S-Band	2200-2499 MHz
LS = Dual L/S Bands	1700-1850/2200-2499 MHz
C1 = Lower C-Band	4400-4900 MHz
C2 = Upper C-Band	4900-4999 MHz
C3 = Full C-Band	4400-4999 MHz
ZZ = Custom	Specify

Frequency

(Fixed Frequency Only)

Enter the Frequency in MHz
(0000.00M format)

or

Custom Options
Consult factory for
available options

Local Signal Strength Indication

C = LCD Meters
E = LED Bars
X = None



Series

Chassis Finish

G = Gold Iridite
N = Nickel Plated

Communication Interface

R = RS-232
T = TTL (3.3V)
2 = RS-422 (Differential)

Frequency Selection

C = Channelized (Local/Preset/Remote)
R = Remote Only

Audio

X = None
S = Stereo Audio (Line/Mic)

Default Video Standard

N = NTSC / 525-Line Pre-Emphasis
P = PAL / 625-Line Pre-Emphasis

Notes:



Advanced Microwave Products
PO Box 1437
2465 Old Highway 40 West, Suite 200
Verdi, NV 89439

Phone: (775) 345-9933
Fax: (775) 345-9913
E-mail: sales@advmw.com
Web: www.advmw.com