

PMT1 Model Number Builder

Micro PCB Video/Audio/Data Transmitter

Frequency Band

U1 = UHF Band	340.0-399.9 MHz
L1 = Lower L-Band	1435-1535 MHz
L2 = Upper L-Band	1700-1850 MHz
S1 = S-Band	2200-2399 MHz
S2 = ISM S-Band	2400-2499 MHz
S3 = Full S-Band	2200-2499 MHz
C1 = Lower C-Band	4400-4900 MHz
C2 = Upper C-Band	4900-4999 MHz
C3 = Full C-Band	4400-4999 MHz
58 = ISM 5.8 GHz	5725-5875 MHz
ZZ = Custom	Specify

Subcarrier Frequency

X = None	6 = 7.20 MHz
1 = 5.80 MHz	7 = 7.50 MHz
2 = 6.00 MHz	8 = 8.30 MHz
3 = 6.20 MHz	9 = 8.59 MHz
4 = 6.50 MHz	Z = Custom
5 = 6.80 MHz	

Frequency

(Fixed Frequency Only)
Enter the Frequency in MHz
(0000.00M format)

or

Custom Options

Consult factory for available options

RF Power Output

Q = 250 mW
W = 20 mW



Series

Communication Interface

R = RS-232
T = TTL (3.3V)

Frequency Selection

C = Channelized (Preset/Remote)
R = Remote Only

Video Standard

N = NTSC / 525-Line Pre-Emphasis
P = PAL / 625-Line Pre-Emphasis

Subcarrier Type

X = None
A = Audio (Line/Mic Selectable)
D = Data (RS-232/TTL (3.3V) Selectable)

Notes:



Advanced Microwave Products
PO Box 1437
2465 Old Highway 40 West, Suite 200
Verdi, NV 89439

Phone: (775) 345-9933
Fax: (775) 345-9913
E-mail: sales@advmw.com
Web: www.advmw.com