

PSR1 Model Number Builder

PCB Video/Audio/Data Receiver

Frequency Band

U1	= UHF Band	340.0-399.9 MHz
L1	= Lower L-Band	1435-1535 MHz
L2	= Upper L-Band	1700-1850 MHz
S1	= S-Band	2200-2399 MHz
S2	= ISM S-Band	2400-2499 MHz
S3	= Full S-Band	2200-2499 MHz
C1	= Lower C-Band	4400-4900 MHz
C2	= Upper C-Band	4900-4999 MHz
C3	= Full C-Band	4400-4999 MHz
58	= ISM 5.8 GHz	5725-5875 MHz
ZZ	= Custom	Specify

Subcarrier Frequency

X	= None	6	= 7.20 MHz
1	= 5.80 MHz	7	= 7.50 MHz
2	= 6.00 MHz	8	= 8.30 MHz
3	= 6.20 MHz	9	= 8.59 MHz
4	= 6.50 MHz	Z	= Custom
5	= 6.80 MHz		

Frequency

(Fixed Frequency Only)
 Enter the Frequency in MHz
 (0000.00M format)

or

Custom Options
 Consult factory for
 available options



Series

Communication Interface

R = RS-232
T = TTL (3.3V)

Frequency Selection

C = Channelized (Preset/Remote)
R = Remote Only

Subcarrier Type

X = None
A = Audio (-10 dBV/+4 dBu)
D = Data (RS-232/TTL (3.3V))

Video Standard

N = NTSC / 525-Line Pre-Emphasis
P = PAL / 625-Line Pre-Emphasis

Notes:



Advanced Microwave Products
 PO Box 1437
 2465 Old Highway 40 West, Suite 200
 Verdi, NV 89439

Phone: (775) 345-9933
 Fax: (775) 345-9913
 E-mail: sales@advmw.com
 Web: www.advmw.com