

# ER75 Model Number Builder

## Encrypted Video/Audio Receiver

### Frequency Band (Other Ranges Available)

U = UHF	340.0-399.9 MHz
M = Lower L-band	1435-1535 MHz
L = Upper L-band	1700-1850 MHz
S = S-band	2200-2399 MHz
2 = ISM S-band	2400.00-2499.75 MHz
D = Dual L/S	1700-1850 & 2200-2500 MHz
C = C-band	4400-4999 MHz
P = Public Safety C-band	4940-4990 MHz

### Video Bandwidth / De-Emphasis

N = 4.2 MHz (NTSC) / 525-Line De-Emphasis
P = 5.0 MHz (PAL) / 625-Line De-Emphasis

### Audio Channels<sup>1</sup>

Blank = No Audio
1 = Mono
2 = Stereo

### Frequency

(Fixed Frequency Only)  
Enter the Frequency in MHz  
(0000.00M format)



### Series

### Finish

N = Nickel Plated
B = Black Plated

### RSSI Display

M = Analog Bar Meter
L = LED Light Bar

### Encryption Key

P = Primary Key Only
S = RS-232 Programmable Secondary Key

### Frequency Selectability

F = Fixed Frequency (Specify with Dash Number)
C = Channelized (RS-232, BCD, and Programmable Switch)

### Notes:

1) Receiver may be configured as video only or with up to two audio channels.



Advanced Microwave Products  
7025 Longley Lane, Suite 20  
Reno, NV 89511

Phone: (775) 345-9933  
Fax: (775) 345-9913  
E-mail: sales@advmw.com  
Web: www.advmw.com